

XL SERIES DATA LOGGERS

DATA COLLECTION PLATFORM (DCP)



H-522+ XL
Data Logger

The **XL Data Logger** series is an extremely reliable and proven Data Collection Platform (DCP), consisting of four models. The H-500XL, H-350XL, H-522, and H-522+ accommodate various applications for remote operation. Collect reliable data under extreme environmental conditions, communicate with satellite, GPRS/GSM modems and other means of communication with the XL Data Logger series.

Key Features

- Simple, menu-driven user interface
- Low standby power
- External button for easy access to current data
- USB Type A Host and Mini B Device (2.0)
- Three RS-232 Serial Ports
- Four analog inputs
- SDI-12 Master or Slave mode
- Quadrature shaft encoder input/output
- Data logging using nonvolatile internal storage
- XL Basic Programming
- Internal Satellite Transmitter



a xylem brand

XL Series Data Loggers

SPECIFICATIONS D17-11

PERFORMANCE		
Pressure Transducer (H-350XL Only)	Accuracy	Less than or equal to 0.02% of full scale output (FSO) over temperature range.
	Range	0 to 103.42 kPa (15 psi) (0 to 11 m (34 ft)) Accuracy: ± 2.1 mm (0.007 ft) 0 to 206.84 kPa (30 psi) (0 to 21 m (69 ft)) Accuracy: ± 4.3 mm (0.014 ft) Custom calibration ranges available to 689 kPa (100 psi)
	Media Compatibility	Non-corrosive dry gases only
Analog Inputs	Channels	4 single ended, 1 differential
	Resolution	24-Bit Resolution
	Accuracy	$\pm 0.02\%$ FS
	Range	0 to 5 Volts (all channels) 0 to 500 mV (additional on channel1)
+5.0 Volt Excitation	Accuracy	± 5.0 mV over load and temperature range
	Current	10 mA (max load)
Switched +12.0 Volt Excitation	Type	Unregulated based on battery voltage
	Current	2.5 Amps
Frequency Input	Range	1 to 10 KHz at ± 75 mVolts PP or greater 1 to 20 KHz at ± 1 Volt PP or greater
	Amplitude	± 5.0 V Max
	Accuracy	$\pm 0.1\%$
Counter Input	Type	Switch closure or voltage pulse
	Voltage Input	0-5 Volts
	Frequency Input	100 Hz (max)
Digital I/O	Channels	2, Independently configured for Input or Output
	Input Levels	0.0 to 0.5 Volts High = 3.5 Volts or higher Low = 0.8 Volts or less
	Output Levels	High = 3.5 Volts Min sourcing 5 mA Low = 0.4 Volts Max sinking 5 mA
4-20 mA Output	Accuracy	$\pm 0.5\%$ FSO
SDI-12	Supports both Master and Slave modes	
	Connector	3-pin connector
RS-232	Type	3 RS-232 communication ports
	Connector	9-pin D connector, female
	Baud Rate	Programmable
MEMORY		
General	Data Storage Capacity	256 MB, Non-Volatile FLASH
COMMUNICATION		
USB	Type	1 host USB-A connector 1 device Mini-B connector
	Version	USB version 2.0
External Satellite	Type H-350/H-500	GOES/METEOSAT/INSAT H-2221-V2
Keypad Display	Type	1 Line 20 Character Vacuum Florescent LED Display

POWER		
Voltage Input	H-350/H-500	10.0 to 16.0 Volts
	H-522+	11.0 to 16.0 Volts
Current	H-350/H-500	Standby: 5 mA Max Active: 270 mA Average
	H-522/ H-522+	Standby: 12 mA Max Active: Transmitting: <2.75 A

ENVIRONMENTAL		
General	Operating Temperature	- 40 to +60°C
	Storage Temperature	- 40 to +80°C
	Humidity	100% non-condensing

PHYSICAL		
Size	Housing H-350/H-500/ H-522	180 mm L x 220 mm W x 110 mm H (7 in. L x 8.5 in W x 4.3 in H)
	Housing H-522+	241.3 mm L x 279.4 mm W x 152.4 mm H (9.5 in. L x 11 in. W x 6 in. H)
Weight	Shipping H-350/H-500/H-522	2 kg (4.25 lbs)
	Shipping H-522+	3.4 kg (7.5 lbs)
Material	Housing	Fiberglass with clear Lexan® window. *H-522 does not have clear Lexan® window.

WARRANTY	
The XL series of data loggers are warranted against defects in materials and workmanship for two years from the date of shipment. For complete terms and conditions, visit: http://www.ysi.com/terms-and-conditions.php	
Note	For detailed specifications, see user manual. Specifications subject to change without prior notice due to on-going commitment to product testing and improvements.

QUICK SPECIFICATION DETAILS				
XL MODEL DIFFERENCES	H-500XL	H-350XL	H-522	H-522+
Keyboard Display	X	X		X
Built-in Pressure Sensor		X		
Built in GOES/METEO-SAT/INSAT satellite transmitter			X	X

YSI, a Xylem brand
1725 Brannum Lane
Yellow Springs, OH 45387

+1.937.767.7241
info@ysi.com
YSI.com



YSI.com/H-522